

Company Profile

Founded in 2013, Qinhuangdao Lingdong conveyer Belt Co.Ltd is a manufacture and exporter specialized in the fabrication of light weight conveyer belting and industrial conveyer products, such as corrugator needle belts; corrugator woven belts , Kevlar woven belts and some tailor made heat resistant kevlar parts for hot handling and conveyance in the glass industry markets.

The company was equipped with two advanced needle corrugated belt and four woven belt producing lines with annual productivity more than 60000 square meters and managed by a group of qualified engineers. With highly-trained technicians available and a staff with more than 10 years of belting experience, Lingdong belts can surely provide you the value-added products and services. Our objective is to acknowledge our customers' needs and to produce and deliver products which meet their requirements.

Contact us now to see how we can help you. Every member of Lingdong team is dedicated to making sure that all of your corrugators needs are met easily, conveniently, and timely. We would like our company to be regarded as a solid and reliable partner.

Lingdong Conveyer makes it easy to choose the right belt for your corrugators!





Qinhuangdao Lingdong Conveyor Belt Co.,Ltd.

Add: No.221,First Section.North Zhangzhuang,Beigang Town, Haigang District Qinhuangdao,Hebei

Web: www.ldconveyor.com **E-mail:** info@ldconveyor.com

Tel:+ 86 335 3647603 **Fax:** + 86 335 8364857

Woven Series



Double Facer Belt

Technical Parameters of Woven Corrugator Belt

Description	Woven Series Conveyer Belt
Raw Materials	100% Synthetic Fiber
Thickness	9-10mm±0.3mm
Width	1400mm-2800mm
Temperature Tolerance	a) 160°C
	b) 200°C
	c) 254°C
Density	7.2±0.3kg/m ²
Air Permeability	1.5*10 ³ cm ³ /(cm ² .min.Kpa)
Coefficient Of Friction	≥0.42 μ
Tensile Strength	70Mp
Speed of Conveyor applicable	240m/min
Lifetime	60-90 million meter
Notes: a)Temperature for long time operation b)Temperature for instantaneous operation c) Melting point	



Qinhuangdao Lingdong Conveyor Belt Co.,Ltd.

Add: No.221,First Section.North Zhangzhuang,Beigang Town, Haigang District Qinhuangdao,Hebei

Web: www.ldconveyor.com **E-mail:** info@ldconveyor.com

Tel:+ 86 335 3647603 **Fax:** + 86 335 8364857

Needle Series



Double Facer Belt



Technical Parameters of Needle Corrugator Belt

Description	Needle Series Conveyor Belt
Raw Materials	100% Synthetic Fiber
Thickness	10mm±0.3mm
Width	1400mm-2800mm
Temperature Tolerance	a) 160°C
	b) 200°C
	c) 254°C
Density	5.5±0.3kg/m ²
Air Permeability	1.0*10 ³ cm ³ /(cm ² .min.Kpa)
Coefficient Of Friction	≥0.32 μ
Tensile Strength	70Mp
Seam	Fasteners made by U.S.
Speed of Conveyor applicable	240m/min
Lifetime	60-90 million meter

Notes: a)Temperature for long time operation
 b)Temperature for instantaneous operation
 c) Melting point